



JMSL1018PP

Features

- Excellent $R_{DS(ON)}$ and Low Gate Charge
- 100% UIS Tested
- 100% Vds Tested
- Halogen-free; RoHS-compliant
- Pb-free plating

Applications


- Load Switch
- PWM Application
- Power Management

Product Summary


Parameters	Value	Unit
V_{DSS}	100	V
$V_{GS(th_Typ)}$	1.7	V
$I_D(@V_{GS}=10V)$	8.4	A
$R_{DS(ON_Typ)}(@V_{GS}=10V)$	14.7	mΩ
$R_{DS(ON_Typ)}(@V_{GS}=4.5V)$	22.2	mΩ



SOP-8



Pin Assignment



Schematic Diagram

Ordering Information

Device	Marking	MSL	Form	Package	Reel(pcs)	Per Carton (pcs)
JMSL1018PP-13	SL1018P	3	Tape&Reel	SOP-8	4000	48000

Absolute Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit
V_{DS}	Drain-to-Source Voltage	100	V
V_{GS}	Gate-to-Source Voltage	± 20	V
I_D	Continuous Drain Current	$T_A = 25^\circ\text{C}$	8.4
		$T_A = 100^\circ\text{C}$	5.3
I_{DM}	Pulsed Drain Current ⁽¹⁾	Refer to Fig.4	A
E_{AS}	Single Pulsed Avalanche Energy ⁽²⁾	74	mJ
P_D	Power Dissipation	$T_A = 25^\circ\text{C}$	2.5
		$T_A = 100^\circ\text{C}$	1.0
T_{J_STG}	Junction & Storage Temperature Range	-55 to 150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Max	Unit
R	Thermal Resistance, Junction to Ambient ⁽³⁾	50	$^\circ\text{C}/\text{W}$




Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics					
V _{(BR)DSS}		100	-	-	V
I _{DSS}		-	-	1.0	P
I _{GSS}		-	-	±100	
V _{GS(th)}		1.2	1.7	2.2	V
		-	14.7	19.1	m :
		-	22.2	28.9	m :
R _g		-	2	-	:
C _{iss}		-	707	1061	pF
C _{oss}		-	357	535	pF
C _{rss}		-	9	-	pF
Q _g		-	13	-	nC
Q _{gs}		-	2.8	-	nC
Q _{gd}		-	2.9	-	nC
t _{d(on)}		-	6.4	-	ns
t _r		-	27	-	ns
t _{d(off)}		-	18	-	ns
t _f		-	8.0	-	ns
I _S		-	-	8.4	A
I _{SM}		-	-	34	A
V _{SD}		-	-	1.2	V
t _{rr}		23	38	58	ns
Q _{rr}		-	21	-	nC

- Notes:
1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.
 2. E_{AS} condition: Starting T_J

Typical Performance Characteristics

Figure 5: Output Characteristics





Typical Performance Characteristics

Figure 11: Normalized Breakdown voltage vs. Junction Temperature




Figure 12: Normalized on Resistance vs. Junction Temperature




Figure 13: Normalized Threshold Voltage vs. Junction Temperature




Figure 14: R_{DS(ON)} vs. V_{GS}





Figure 15: Maximum Safe Operating Area



Test Circuit



Figure 1: Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveform




Figure 3: Unclamped Inductive Switching Test Circuit & Waveform





Figure 4: Diode Recovery Test Circuit & Waveform






Package Mechanical Data(SOP-8)

Package Outline



DIM	MILLIMETER		
	MIN.	NOM.	MAX.
A	1.35	1.50	1.65
A1	0.05	0.10	0.15
A2	1.35	1.40	1.50
b	0.38	--	0.50
c	0.17	--	0.25
D	4.80	4.90	5.00
E	5.80	6.00	6.20
e1	3.80	3.90	4.00
e2	1.27(BSC)		
e3	0.45	0.60	0.80
e4	1.04 REF		
e5	0.25 BSC		
e6	0.30	0.40	0.50
θ1	0°	--	8°
θ2	10°	12°	14°
θ3	8°	10°	12°
θ4	10°	12°	14°
θ5	8°	10°	12°

Recommended Footprint



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

 is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.