Features

- High Power Density
- High mechanical robustness
- Compact design
- Isolated heatsink using DBC technology
- Very low forward voltage drop
- Fast & soft reverse recovery anti-parallel FWD

Product Summary

Applications

- Active Rectifier
- Air Conditioning
- Motor Drives

IGBT, Inverter Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Collector-emitter voltage	T_{vj} = 25°C	V_{CES}	1200	V
Continuous collector current	T_C = 25°C, T_{vj} = 175°C	I_C	28	A

Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers

IGBT, Inverter Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions		Symbol	Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	I_C = 15A, V_{GE} = 15V	T_{vj} = 25°C	$V_{CE(sat)}$		1.85	2.25	V
		T_{vj} = 125°C			2.30		
		T_{vj} = 150°C			2.35		
Gate threshold voltage	V_{CE}=V_{GE}, I_C=0.3mA		$V_{GE(th)}$	5.2	5.8	6.4	V
Gate-emitter leakage current	V_{CE} = 0V, V_{GE} = 20V		I_{GES}			400	nA
Collector leakage current	V_{CE}=1200V V_{GE}=0V		I_{CES}			1	mA
Input capacitance	f = 1MHz, T_{vj} = 25°C, V_{CE} = 25 V, V_{GE} = 0 V		C_{ies}		0.89		nF
Output capacitance			C_{oes}		0.03		nF
Gate charge	V_{GE} = -15V…+15V		Q_G		0.12		uC
Turn-on delay time, inductive load	V_{CE} = 600V, I_C = 15A , R_G = 51 Ÿ V_{GE} = ±15V , T_{vj} = 25 (		$t_{d(on)}$		98.4		ns
Rise time, inductive load			t_r		98.2		ns
Turn-off delay time, inductive load			$t_{d(off)}$		114		ns
Fall time, inductive load			t_f		174		ns
Turn-on energy loss per pulse			E_{on}		1.81		mJ

Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers

FRED, Inverter Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
RepetitiveVaÍpeR1Tw 40 vVaFRR				

Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers

IGBT, Brake-Chopper Electrical Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Collector-						

Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers

FRED, Brake-Chopper Absolute Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit

Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers

NTC-Thermistor Characteristics (@ T_C = 25°C unless otherwise specified)

Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	

Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers

Fig 5. FRED Foward Characteristics, Inverter(typcial)



Fig 6. FRED Forward Characteristics, Inverter(typcial)



Fig 7. Diode Rectifier Forward Characteristics



Jiangsu JieJie Microelectronics Co., Ltd.
All product information are copyrighted and subject to legal disclaimers