









**ORDERING INFORMATION**


**FIG.1:** Maximum power dissipation versus RMS on-state current




**FIG.3:** Surge peak on-state current versus number of cycles



**FIG.2:** RMS on-state current versus case temperature



**FIG.4:** On-state characteristics

**FIG.7** Test circuit for inductive and resistive loads to IEC-61000-4-5 standards


**ORDERING INFORMATION**

| Order code    | Voltage<br>$V_{\text{DRM}}/V_{\text{RRM}}$ (V) | IGT(mA) | Package | Base qty.<br>(pcs) | Delivery<br>mode |
|---------------|------------------------------------------------|---------|---------|--------------------|------------------|
| ACJT08H-800SW | 800                                            | 10      | TO-251  | 80                 | Tube             |

**Document Revision History**

| Date         | Revision | Changes                        |
|--------------|----------|--------------------------------|
| Apr.14, 2023 | A.1.0    | Last updated                   |
| Oct.20, 2025 | A.1.1    | Revise PACKAGE MECHANICAL DATA |

PACKAGE MECHANICAL DATA





Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.