

JX006U

Peak gate power	P _{GM}	0.5	W
Peak pulse voltage (T _j =25℃ ; non-repetitive,off-state;FIG.7)	V _{pp}	0.5	kV

NOTE 1: Operating junction temperature T_j is up to 125℃ when a resistor ≤1kΩ is connected between Gate and Cathode. Without this resistor, the T_j is up to 110℃ only.

① Z_{ds(on)} is less than 10mΩ unless otherwise specified.

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	

K Z Z / E ' / E & K Z D d / K E

J	X	006	U	-/
JieJie Microelectronics Co., Ltd.				Blank: Bulk Pack -TR: Tape & Reel
Sensitive gate SCRs				
		Part number		
			U:TO-92	

D Z < / E '


	<table border="0"> <tr> <td>Year</td> <td>_____</td> <td>_____</td> <td>Production</td> </tr> <tr> <td>Month</td> <td>_____</td> <td>_____</td> <td>Code</td> </tr> </table>	Year	_____	_____	Production	Month	_____	_____	Code
Year	_____	_____	Production						
Month	_____	_____	Code						

FIG.1: Maximum power dissipation versus
RMS on-state current

FIG.2: RMS on-state current versus case
temperature





FIG.7 ÖTest circuit for inductive and resistive loads to IEC-61000-4-5 standards.




K Z Z / E ' / E & K Z D d / K E

Order code	Voltage V _{DRM} /V _{RRM} (V)	IGT(▷A)	Package	Base qty. (pcs)	Delivery mode
JX006U	600	ô80	TO-92	1,000	Bulk Pack
JX006U-TR				2,000	Tape & Reel

Document Revision History

Date	Revision	Changes
------	----------	---------


W < ' D , E / > d



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.45					
B	4.32					
C	3.1	U	1	f.		
D		M	N	▶	1	
E						
F						
G						
H						
J						
K						
N						
P						
V						

>/s Zz DK

PACKAGE	OUTLINE	BAG (PCS)	INNER BOX (PCS)	CARTON BOX (PCS)
TO-92	Bulk Pack	1,000	10,000	50,000



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
P	12.40	12.70	13.00	0.488	0.500	0.512
P0	12.40	12.70	13.00	0.488	0.500	0.512
P1	3.55	3.85	4.15	0.140	0.152	0.163
P2	5.95	6.35	6.75	0.233	0.250	0.265
, P	-1.00	0	1.00	-0.039	0	0.039
F1 ~F2	2.30	2.50	2.70	0.090	0.098	0.106
F1-F2	-0.10	0	0.10	-0.004	0	0.004
W	17.50	18.00	19.00	0.689	0.709	0.748
W0	5.50	6.00	6.50	0.217	0.236	0.256
W1	8.50	9.00	9.50	0.335	0.354	0.374
W2			1.00			0.039
D0	3.80	4.00	4.20	0.150	0.157	0.165
, H	-1.00	0	1.00	-0.039	0	0.039
L1	2.50			0.098		
H	18.00	19.00	20.00	0.709	0.748	0.787
H1 ~H2			3.00			0.119

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.
Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.