



T3050H-6F 30A TRIAC

Rev.A.1.1

DESCRIPTION:

The T3050H-6F triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. Compared to traditional triacs, T3050H-6F provides a very high switching capability up to junction temperatures of 150°C. B

Average gate power dissipation ($T_j=150\text{ }^{\circ}\text{C}$)	$P_{G(AV)}$	1	W
Peak gate power	P_{GM}	10	W
Peak pulse voltage ($T_j=25\text{ }^{\circ}\text{C}$; non-repetitive, off-state; FIG. 7)	V_{pp}	1.2	kV

ELECTRICAL CHARACTERISTICS ($T_j=25\text{ }^{\circ}\text{C}$ unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	$V_D=12V\ R_L=33\Omega$	- -	MAX.	50	mA
V_{GT}		- - 8	MAX.	1.3 0	V

ORDERING INFORMATION

T	30	50	H	-6	F
Triacs	$I_{T(RMS)}: 30A$				F: TO-220F(Ins)
	$50: I_{GT1-3} \leq 50mA$			$6: V_{DRM} / V_{RRM} \geq 600V$	
			High junction temperature		

MARKING




FIG.1: Maximum power dissipation versus RMS on-state current




FIG.3: Surge peak on-state current versus number of cycles




FIG.2: RMS on-state current versus case temperature




FIG.4: On-state characteristics





FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards




ORDERING INFORMATION

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		[-] - -			
T3050H-6F	600	50	TO-220F(Ins)	50	Tube

Document Revision History

Date	Revision	Changes
Apr.10, 2023	A.1.0	Last updated

PACKAGE MECHANICAL DATA



/

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.