



JST08C-600SW 8A TRIAC

Rev.A.1.1

DESCRIPTION:

C0 Tc 1 T4 -0.00 0 0 14.04

The JST08C-600SW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST08C-600SW

snubberless (es64.1 Tw [(Td [(60)10 (t0 Tc 0 Tw 2.3 M286)6.9 (s)4.1 (.) c)4 (i)6)1 (C)6 (ia0)-11c1

Peak gate power	P_{GM}	10	W
Peak pulse voltage ($T_j=25$; non-repetitive,off-state;FIG.7)	V_{pp}	1.5	kV

ELECTRICAL CHARACTERISTICS (unless otherwise specified)

Symbol Test Condition Quadrant u -96

ORDERING INFORMATION

	J	ST	08	C	-600	SW
JieJie Microelectronics Co., Ltd.		Triacs				

600:V-42 2 4308C6

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.